


## Reflectors

### Specifications

Order code	Description	Watts (energy used)	Base type	Luminous intensity (cd)	Life (hours)	Colour temp (°k)	CRI	MOL (mm)	Max diameter (mm)	Weight (g)
<b>HALOGEN SAVER REFLECTOR R50 &amp; R63</b>										
HSR5018E14 230V/240V	18W HALOGEN SAVER R50 E14 230V/240V	18	E14	210	2000	2800K	100	86,5	51	18
HSR5018B15 230V/240V	18W HALOGEN SAVER R50 B15 230V/240V	18	B15	210	2000	2800K	100	86,5	51	21
HSR5028E14 230V/240V	28W HALOGEN SAVER R50 E14 230V/240V	28	E14	430	2000	2800K	100	86,5	51	18
HSR5028B15 230V/240V	28W HALOGEN SAVER R50 B15 230V/240V	28	B15	430	2000	2800K	100	86,5	51	21
HSR5042E14 230V/240V	42W HALOGEN SAVER R50 E14 230V/240V	42	E14	580	2000	2800K	100	86,5	51	18
HSR5042B15 230V/240V	42W HALOGEN SAVER R50 B15 230V/240V	42	B15	580	2000	2800K	100	86,5	51	21
HSR6328E27 230V/240V	28W HALOGEN SAVER R63 E27 230V/240V	28	E27	600	2000	2800K	100	105	64	40
HSR6328B22 230V/240V	28W HALOGEN SAVER R63 B22 230V/240V	28	B22	600	2000	2800K	100	105	64	42
HSR6342E27 230V/240V	42W HALOGEN SAVER R63 E27 230V/240V	42	E27	960	2000	2800K	100	105	64	40
HSR6342B22 230V/240V	42W HALOGEN SAVER R63 B22 230V/240V	42	B22	960	2000	2800K	100	105	64	42
HSR6353E27 230V/240V	53W HALOGEN SAVER R63 E27 230V/240V	53	E27	1100	2000	2800K	100	105	64	40
HSR6353B22 230V/240V	53W HALOGEN SAVER R63 B22 230V/240V	53	B22	1100	2000	2800K	100	105	64	42
<b>HALOGEN SAVER REFLECTOR GU10</b>										
HS28GU10 230V/240V	28W HALOGEN SAVER REFLECTOR GU10 230V/240V	28	GU10	600	2000	2800K	100	57	51	44
HS40GU10 230V/240V	40W HALOGEN SAVER REFLECTOR GU10 230V/240V	40	GU10	900	2000	2800K	100	57	51	44
<b>HALOGEN REFLECTOR MR16</b>										
H20MR16 12V	20W HALOGEN MR16 12V	20	MR16	650	3000	2800K	100	46	51	32
H35MR16 12V	35W HALOGEN MR16 12V	35	MR16	1200	3000	2800K	100	46	51	32
H50MR16 12V	50W HALOGEN MR16 12V	50	MR16	1800	3000	2800K	100	46	51	32



REFLECTOR E14



REFLECTOR